

# TOSAKI

## PW180

Operating Conditions

## High Pressure Washer



### Standard features

- Four poles electric motor fits overload protection
- Motor with aluminum casing
- Commercial grade direct drive brass cylinder ceramic plungers radial direction pump
- 8m high-pressure hose
- Quick connect nozzles 0 , 15 , 25(85) , 40
- Pressure adjustable
- Professional trigger gun with safety lock
- 8-inch Semi-filled wheel
- In-line water filter
- Convenient hose and gyn hook
- Water inlet hoseconnector
- Plastic cover

### Optional

- Custom-made motor Voltage and Frequency
- Protection box
- 5m cable

### Protection box

- Industry waterproof on-off switch easy turn on and off the motor
- Motor over-load protector is available

### Protection box

- Material PP+GF30%



### Overall & Installation Dimensions

| Model      | Electric Motor (kW) | Voltage (V) | Revolution (rpm) | Max.Pressure |      | Flow  |      | Pump Model | Packing Dim. (cm) | Gross Weight (kg) |
|------------|---------------------|-------------|------------------|--------------|------|-------|------|------------|-------------------|-------------------|
|            |                     |             |                  | bar          | PSI  | L/min | GPM  |            |                   |                   |
| PW-180-3.7 | 3.7                 | 220         | 2900             | 180          | 2600 | 10.7  | 2.84 | 3WZ-1507C  | 67x53x46          | 57                |